



BOND TUF CRACK SEAL

Single Component Acrylic Sealant For Internal And External Cracks

BOND TUF CHEMICALS PVT. LTD.

AN ISO 9001 : 2015 COMPANY

www.bondtuf.com

BONDTUF CRACK SEAL

Single Component Acrylic Sealant For Internal And External Cracks

DESCRIPTION

BONDTUF CRACK SEAL is a crack filling material for plaster & concrete cracks, based on acrylic emulsion. BONDTUF CRACK - SEAL is used to give a thin render coat to level out surface.

ADVANTAGES / BENEFITS

BONDTUF CRACK SEAL gives smooth finish to the surface. BONDTUF CRACK SEAL has excellent adhesive property. BONDTUF CRACK SEAL has high tensile strength. BONDTUF CRACK SEAL has no shrinkage.

COVERAGE

6 TO 7 Sq. mt. Per Kg for 6mm Groove

AREAS OF APPLICATION

BONDTUF CRACK SEAL is used in external & internal cracks in plastered masonry surface. BONDTUF CRACK SEAL is used to give a thin render coat to even out surface.

DIRECTIONS FOR USAGE

Clean the joints, cracks, gaps from dust, oil, grease and loose particles. Pre wet the crack with water for porous surfaces. Fill the joints, cracks, gaps by putty knife or spatula. Avoid formulation of bubbles or cavities while applying. After application leave the surface for at least one day. Apply second coat of BONDTUF CRACK SEAL if shrinkage is noticed. Allow it to dry for 1 to 3 hrs. Before painting work is taken up.

PRECAUTIONS

BONDTUF CRACK SEAL should be removed from the tools at the earliest before it hardens by cleaning with water. BONDTUF CRACK SEAL is non-toxic, non-flammable. Splashes on to skin if any should be washed with plenty of water. When it comes in contact with eyes, wash with water and take medical advice.

SUPPLY

BONDTUF CRACK SEAL Come's in 1 Kg Packs.

SHELF LIFE

1 year (to be stored in cool and dry place)

BONDUF CRACK SEAL

Single Component Acrylic Sealant For Internal And External Cracks

TECHNICAL SUPPORT

Bondtuf provides a technical advisory service for on-site assistance and advice on admixture selection, evaluation trials and dispensing equipment. Technical data and guidance can be provided for admixtures and other products for use with fresh and hardened concrete.

IMPORTANT NOTE

Bondtuf products undergo high standard quality checks and every reasonable precaution is taken in the manufacture of all products. BONDUF continuously strive to ensure the products, recommendations, specification & information given is reliable, correct and accurate. No specific guarantee can be assured as product performance depends not only on quality but also on many other factors which are not under our control. The customer should make his own trails to determine the compatibility of the product for his own purpose. All products are sold subject to our standard terms and conditions of sale.

BONDUF PRODUCT RANGE

WATERPROOFING COMPOUNDS | REPAIRS & REHABILITATION AGENTS | ADMIXTURES & CONCRETE TREATMENT
FOUNDATION GROUTS & FLOOR HARDENER | EPOXY COATINGS & SCREEDS | TILE & STONE FIXING ADHESIVES